

Description

■ 60W □ 90mm

系列 Series	型号Model · 类型 Type		输出功率 Output power	电压 Voltage	频率 Frequency	电流 Current	启动转矩 Starting Torque	额定转矩 Rated Torque	额定转速 Rated Speed	电容器容量 Capacitor
	上段:齿轮轴 下段()内:圆轴	Upper:Pinion Shaft Below:Round Shaft								
	导线型 Lead Wire Type	带端子箱型 Terminal Box Type								
	外形图Dimensions①	外形图Dimensions②								
感应电动机 Induction motors	5IK60GN-AF (5IK60A-AF)	5IK60GN-AFT (5IK60A-AFT)	60	1ph 100	50	1.00	320	470	1250	20.0
					60	1.10		380	1550	
	5IK60GN-EF (5IK40A-EF)	5IK60GN-EFT (5IK60A-EFT)	60	1ph 110	60	0.80	300	380	1550	12.0
				1ph 120		0.85				
	5IK60GN-CF (5IK60A-CF)	5IK60GN-CFT (5IK60A-CFT)	60	1ph 220	50	0.50	340	470	1250	4.0
				1ph 230		0.55				
	5IK60GN-HF (5IK60A-HF)	5IK60GN-HFT (5IK60A-HFT)	60	1ph 220	60	0.50	340	380	1550	
				1ph 230		0.55				
	5IK60GN-SF (5IK60A-SF)	5IK60GN-SFT (5IK60A-SFT)	60	3ph 220	50	0.45	1000	470	1250	-
					60	0.40	800	380	1550	
可逆电动机 Reversible motors	5RK60GN-AF (5RK60A-AF)	5RK60GN-AFT (5RK60A-AFT)	60	1ph 100	50	1.26	470	470	1250	25.0
					60	1.70		380	1550	
	5RK60GN-EF (5RK60A-EF)	5RK60GN-EFT (5RK60A-EFT)	60	1ph 110	60	1.05	330	380	1550	15.0
				1ph 120			380			
	5RK60GN-CF (5RK60A-CF)	5RK60GN-CFT (5RK60A-CFT)	60	1ph 220	50	0.55	420	470	1250	4.5
				1ph 230		0.60	460			
	5RK60GN-HF (5RK60A-HF)	5RK60GN-HFT (5RK60A-HFT)	60	1ph 220	60	0.55	420	380	1550	4.5
				1ph 230		0.60	460			