

■ 40W □ 90mm

系列 Series	型号Model · 类型 Type		输出功率 Output power	电压 Voltage	频率 Frequency	电流 Current	启动转矩 Starting Torque	额定转矩 Rated Torque	额定转速 Rated Speed	电容器容量 Capacitor
	上段:齿轮轴 Upper:Pinion Shaft	下段()内:圆轴 Below:Round Shaft								
	导线型 Lead Wire Type	带端子箱型 Terminal Box Type								
	外形图Dimensions①	外形图Dimensions②								
感应电动机 INduction motors	5IK40GN-A (5IK40A-A)	5IK40GN-AT (5IK40A-AT)	40	1ph 100	50	0.65	220	315	1250	12.0
					60	0.70		260	1550	
	5IK40GN-E (5IK40A-E)	5IK40GN-ET (5IK40A-ET)	40	1ph 110	60	0.55	200	260	1550	8.0
				1ph 120		0.60				
	5IK40GN-C (5IK40A-C)	5IK40GN-CT (5IK40A-CT)	40	1ph 220	50	0.35	220	315	1250	2.5
				1ph 230		0.40				
	5IK40GN-H (5IK40A-H)	5IK40GN-HT (5IK40A-HT)	40	1ph 220	60	0.35	200	260	1550	-
				1ph 230		0.40				
可逆电动机 Reversible motors	5RK40GN-A (5RK40A-A)	5RK40GN-AT (5RK40A-AT)	40	1ph 100	50	0.78	300	315	1250	15.0
					60	1.05		260	1550	
	5RK40GN-E (5RK40A-E)	5RK40GN-ET (5RK40A-ET)	40	1ph 110	60	0.79	260	260	1550	12.0
				1ph 120		0.80				
	5RK40GN-C (5RK40A-C)	5RK40GN-CT (5RK40A-CT)	40	1ph 220	50	0.45	270	315	1250	3
				1ph 230						
	5RK40GN-H (5RK40A-H)	5RK40GN-HT (5RK40A-HT)	40	1ph 220	60	0.45	270	260	1550	3
				1ph 230						