

120W 90mm

系列 Series	型号Model · 类型 Type		输出功率 Output power	电压 Voltage	频率 Frequency	电流 Current	启动转矩 Starting Torque	额定转矩 Rated Torque	额定转速 Rated Speed	电容器容量 Capacitor
	上段:齿轮轴 Upper:Pinion Shaft	下段()内:圆轴 Below:Round Shaft								
	导线型 Lead Wire Type	带端子箱型 Terminal Box Type								
	外形图Dimensions①	外形图Dimensions②								
感应电动机 INduction motors	5IK120GU-AF (5IK120A-AF)	5IK120GU-AFT (5IK120A-AFT)	120	1ph 100	50	2.1	600	930	1250	30.0
					60	2.5		750	1550	
	5IK120GU-EF (5IK120A-EF)	5IK120GU-EFT (5IK120A-EFT)	120	1ph 110	60	1.65	600	750	1550	25.0
				1ph 120		1.80				
	5IK120GU-CF (5IK120A-CF)	5IK120GU-CFT (5IK120A-CFT)	120	1ph 220	50	1.0	650	930	1250	7.0
				1ph 230		0.95				
	5IK120GU-HF (5IK120A-HF)	5IK120GU-HFT (5IK120A-HFT)	120	1ph 220	60	1.0	600	750	1550	
				1ph 230		0.95				
5IK120GU-SF (5IK120A-SF)	5IK120GU-SFT (5IK120A-SFT)	120	3ph 220	50	0.70	1850	930	1250	-	
				60	0.60	1600	750	1550		
可逆电动机 Reversible motors	5RK120GU-AF (5RK120A-AF)	5RK120GU-AFT (5RK120A-AFT)	120	1ph 100	50	2.25	700	930	1250	35.0
					60	2.85		750	1550	
	5RK120GU-EF (5RK120A-EF)	5RK120GU-EFT (5RK120A-EFT)	120	1ph 110	60	1.90	650	750	1550	30.0
				1ph 120			720			
	5RK120GU-CF (5RK120A-CF)	5RK120GU-CFT (5RK120A-CFT)	120	1ph 220	50	1.15	720	930	1250	8.0
				1ph 230						
	5RK120GU-HF (5RK120A-HF)	5RK120GU-HFT (5RK120A-HFT)	120	1ph 220	60	1.20	720	750	1550	8.0
				1ph 230						